


PolyStone™ Grout
PREMIXED INSTRUCTIONS

USE ONLY CRYNTEL POLYSTONE™ PREMIXED GROUT WITH VILLAFLOOR™. THE USE OF A NON-APPROVED GROUT WILL VOID WARRANTY.

DO'S

- DO grout only 4-6 sq ft at a time and clean all grout from tile surface before starting next work area
- DO use rubber grout float
- DO use nylon sponge
- DO wring out sponge thoroughly
- DO use clean cool water for rinsing out sponge
- DO wipe lightly, using as little pressure as possible when cleaning grout
- DO wait 5 days after installation before cleaning off new stains
- DO clean stains from grout with mild soap and water or mild household cleaner

DON'TS

- DON'T spread grout over entire tile surface
- DON'T use sponge made for ceramic tiles
- DON'T make grout line larger than 1/4"
- DON'T forget to change water frequently
- DON'T use traditional ceramic tile grout
- DON'T use acids, vinegar, bleach or other harsh cleaners on grout
- DON'T try to clean stains from grout until it has cured for five (5) days
- DON'T walk on grout for five (5) hours after installation
- DON'T use on ceramic, marble, terrazzo etc.
- DON'T use with any other product other than Cryntel® VillaFloor™ Tiles
- DON'T use high pressure washers, steam cleaners or similar devices

CAUTION: AVOID DIRECT EYE CONTACT. DO NOT TAKE INTERNALLY. WARNING: KEEP OUT OF REACH OF CHILDREN.

ITEMS NEEDED: Large nylon sponge, rubber grout float, cheesecloth, access to cool clean water bucket.

NOTE: DO NOT ADD WATER TO GROUT. Keep at room temperature for 48 hours prior to use.

LIMITATIONS: Do not apply below 60°F or above 90°F. Not for use on grout joints wider than 1/4". Not for outdoor use.

NEW INSTALLATIONS: Wipe tile surface with slightly dampened sponge before grouting. (A slightly dampened surface allows the grout to spread easier into the grout joint lines). Avoid spreading grout over tile surface because this may delay instalprocess. Holding grout float at 45° angle, force grout diagonally into joints ensuring joints are completely filled and flush to the tile surface.

Remove all excess grout by holding float at 90° angle and drawing diagonally across tile.

Apply grout on no more than 4-6 tiles at a time and clean per instructions. To clean, soak grout sponge in cool clean water. Wring out excess water completely. Use damp sponge in circular motion to smooth joints and clean excess grout from tile. Rinse sponge and repeat until all excess grout is removed from tile. Using clean water and sponge will aide in cleanup. Avoid excess water in grout joints. Use damp sponge then soft, clean cloth to polish off residue.

NOTE: PolyStone™ Premixed Stain Repellent Grout is very easy to apply and clean up. Certain adverse application techniques like the use of excess water or cleaning of grout lines too early, may create a situation where some touch up or a second coat may be required. If this happens, let the grout dry thoroughly, then reapply the grout, filling any areas of concern. Clean per original instructions. Unlike traditional grouts, PolyStone™ Premixed Stain Repellent Grout will adhere to itself, so re-grouting is never a problem.

REPAIR EXISTING GROUT: Remove existing old grout with a grout saw 1/16" below the surface of existing tile. Sweep or vacuum dust and debris from surface of tile and grout joints. Follow directions for new installation as shown above. Unlike traditional grout, PolyStone™ Premixed Stain Repellent Grout will adhere to old grout and appear as new.

TAKE CARE: Not to chip or damage the edges of the tiles.

PolyStone™ Premixed, Stain Repellent Grout must cure for FIVE (5) hours before walking on.

PolyStone™ Premixed, Stain Repellent Grout MUST CURE FOR FIVE (5) DAYS FOR STAIN REPELLENT FEATURE TO BE EFFECTIVE.


LIMITED WARRANTY: Cryntel® warrants that, subject to the limitations and conditions set forth herein, PolyStone™ Premixed Stain Repellent Grout (when installed according to package directions) will resist cracking, color fading and most common household stains (qualified stains-caused by common household products used in a kitchen, such as food and bath, such as, personal care products) except those listed (unqualified stains – corrosive products, such as but not exclusively bleach, solvent based cleaners, calcium and lime removers, peroxides, paint removers, indelible/permanent markers) for ten (10) years from date of installation. **NOT WARRANTED FOR USE WITH MARBLE, TERRAZZO, CERAMIC OR ANY OTHER PRODUCT OTHER THAN CRYNTEL® VillaFloor™ Tile. NOT WARRANTED IN WET AREAS SUCH AS SHOWERS AND BACK SPLASHES OR WALL TILES.** For further details on our Warranty and its limitations, contact Cryntel at 800-766-1043

INGREDIENTS: Acrylic-Styrene Copolymer (No CAS#), Propylene Glycol CAS # 57-55-6, Titanium Dioxide CAS # 13463-67-7, Mineral Spirits CAS # 8052-41-3, Silicone Dioxide CAS # 148-60-7, Water CAS # 7732-18-5, Calcium Carbonate CAS # 1317-65-3, VOC: 25g/l. Patent Pending


24-Hour Emergency Phone: CHEMTREC 800-424-9300. Outside USA 703-527-3887.

For technical information or assistance call 800-766-1043.

SPREAD GROUT IN JOINTS



CLEAN UP GROUT



WAIT 5 HOURS TO WALK ON

